














# Armstrong® Strainers ID Charts

Illustration	Model	Connection Size	Connection Type	Body Material	Pressure Temperature Ratings		Located on Page	
					Steam Non-shock	Cold Non-shock		
	CA	1/2", 3/4", 1", 1-1/4", 1-1/2", 2"	Screwed	Cast Iron ASTM-A48 Class 30	250 psig @ 406°F	400 psig @ 150°F	436	
	A	2-1/2", 3"					436	
	A	2"	125 Flanged		125 psig @ 353°F	175 psig @ 150°F	437	
	A	2-1/2" - 6"					437	
	A	2"	250 Flanged		250 psig @ 400°F	400 psig @ 150°F	437	
	A	2-1/2" - 6"					437	
	B	1/2", 3/4", 1"	Screwed & Socketweld 900 lb		1 635 psig @ 609°F	2 220 psig @ 100°F	438	
	B	1-1/4", 1-1/2", 2", 3"	Screwed & Socketweld 600 lb		1 135 psig @ 562°F	1 480 psig @ 100°F	438	
 B	B	1/2", 3/4", 1"	Class 150 Flanged		Cast Carbon Steel ASTM-A216 Gr. WCB	205 psig @ 390°F	285 psig @ 100°F	439
	B	1-1/4", 1-1/2"						439
	YCS-B	2" - 12"		440				
	B	1/2", 3/4", 1"	Class 300 Flanged	605 psig @ 490°F		740 psig @ 100°F	439	
	B	1-1/4", 1-1/2"					439	
	YCS-B	2" - 12"					440	
	 YCS-B	B	1/2", 3/4", 1"	Class 600 Flanged		1 135 psig @ 562°F	1 480 psig @ 100°F	439
		B	1-1/4", 1-1/2"					439
YCS-B		2" - 12"	440					
	C	1/2", 3/4", 1"	Screwed & Socketweld 1 500 lb	Cast Chrome Moly Steel ASTM-A217 Gr. WC6		2 090 psig @ 643°F	3 000 psig @ 100°F	441
	C	1-1/4", 1-1/2", 2"			441			
	C	1/2", 3/4", 1"	Class 1 500 Flanged		2 090 psig @ 643°F	3 000 psig @ 100°F	442	
	C	1-1/4", 1-1/2", 2"			2 515 psig @ 670°F	3 600 psig @ 100°F	441	
	D	1/2", 3/4", 1", 1-1/4", 1-1/2", 2"	Socketweld 2 500 lb		2 500 psig @ 1 025°F	6 000 psig @ 100°F	442	

# Strainers ID Charts

Illustration	Model	Connection Size	Connection Type	Body Material	Pressure Temperature Ratings		Located on Page	
					Steam Non-shock	Cold Non-shock		
	E	1/2", 3/4", 1"	Screwed & Socketweld 1 500 lb	Cast Stainless Steel ASTM-A351 Gr. CF8M	2 090 psig @ 643°F	3 000 psig @ 100°F	443	
	E	1-1/4", 1-1/2", 2", 3"	Screwed & Socketweld 600 lb		935 psig @ 538°F	1 140 psig @ 100°F	443	
	E	1/2", 3/4", 1"	Class 150 Flanged		Cast Stainless Steel ASTM-A351 Gr. CF8M	200 psig @ 386°F	275 psig @ 100°F	444
	E	1-1/2"						444
	YSS-E	2" - 12"						445
	E	1/2", 3/4", 1"	Class 300 Flanged			495 psig @ 467°F	720 psig @ 100°F	444
	E	1-1/2"						444
	YSS-E	2" - 12"						445
	E	1/2", 3/4", 1"	Class 600 Flanged			935 psig @ 540°F	1 440 psig @ 100°F	444
	E	1-1/2"						444
YSS-E	2" - 12"	445						
	F	1/2", 3/4", 1", 1-1/4"	Screwed 300 lb	Cast Bronze ASTM-B62		300 psig @ 422°F	500 psig @ 150°F	446
	F	1-1/2", 2"			446			